



## NXBLE-125G Residual current operated circuit breaker (RCBO)

### 1. Compliant standards

IEC61009-1

### 2. Compliant certification

CE

### 3. Major function

Overload protection, short circuit protection, isolation, residual current operation

### 4. Technical parameters

Rated current: 63A, 80A, 100A(1P+N, 2P, 3P, 4P), 125A(1P+N, 2P)

Rated residual operating current: 0.03A, 0.05A, 0.075A, 0.1A, 0.3A;

Rated voltage: 230V ~ (1P+N, 2P), 400V ~ (3P, 3P+N, 4P);

Frequency: 50Hz

Thermal magnetic release: B, C, D;

Number of poles: 1P+N, 2P, 3P, 3P+N, 4P;

Mechanical life: 20000 cycles;


Electrical life: 6000 cycles ( $I_n \leq 100A$ ); 4000 cycles ( $I_n > 100A$ );

Rated short-circuit breaking capacity( $I_{cn}$ ): 10000A;

Short-circuit breaking capacity( $I_{cs}$ ): 7500A;

Rated impulse withstand voltage( $U_{imp}$ ): 4kV.

### 5. Dimensions and installation sizes



|       | 1P+N                               | 2P                                 | 3P                                 | 4P                                 |
|-------|------------------------------------|------------------------------------|------------------------------------|------------------------------------|
| L(mm) | 54 <sup>0</sup> <sub>-0.74</sub>   | 81 <sup>0</sup> <sub>-0.87</sub>   | 108 <sup>0</sup> <sub>-1.40</sub>  | 35 <sup>0</sup> <sub>-1.60</sub>   |
| H(mm) | 75.5 <sup>0</sup> <sub>-1.20</sub> | 78.5 <sup>0</sup> <sub>-1.20</sub> | 78.5 <sup>0</sup> <sub>-1.20</sub> | 78.5 <sup>0</sup> <sub>-1.20</sub> |