# **CERTIFICATE**

Issued to:
Applicant:
Zhejiang Chint Electrics Co., Ltd.
No. 1, Chint Road,
Chint Industrial Zone,
North Baixiang, Yueqing,
Zhejiang, China

Licensee:
Zhejiang Chint Electrics Co., Ltd.

No. 1, Chint Road, Chint Industrial Zone, North Baixiang, Yueqing, Zhejiang, China

Product : Automatic transfer switching equipment (ATSE)

Trade name(s) : CHINT Type(s)/model(s) : NXZHM-800

The product and any acceptable variation thereto is specified in the Annex to this certificate and the documents therein referred to.

DEKRA hereby declares that the above-mentioned product has been certified on the basis of:

- a type test according to the standard EN 60947-6-1;2005 and EN 60947-6-1;2005/AN;2014
- an inspection of the production location according to CENELEC Operational Document CIG 021
- a certification agreement with the number 2032236

DEKRA hereby grants the right to use the KEMA-KEUR certification mark

The KEMA-KEUR certification mark may be applied to the product as specified in this certificate for the duration of the KEMA-KEUR certification agreement and under the conditions of the KEMA-KEUR certification agreement.

This certificate is issued on 18 June 2018 and expires upon withdrawal of one of the above mentioned standards.

Certificate number: 33-103907

**DEKRA Certification B.V.** 

drs. G.J. Zoetbrood Managing Director Kreny Lin Certification Manager

© Integral publication of this certificate is allowed

ACCREDITED BY THE DUTCH ACCREDITATION COUNCIL







#### SPECIFICATION OF THE CERTIFIED PRODUCT

Product data

Product : Automatic transfer switching equipment (ATSE)

Trade name(s) : CHINT Type(s)/model(s) : NXZHM-800

Class of equipment : PC
Utilization category : AC-33B
Number of poles : 3P, 3P+N
Rated voltage (Ue) : 400 / 415 Vac
Rated insulation voltage (Ui) : 1000 V
Rated impulse withstand voltage : 12 kV

(Uimp)

Rated operational current (le) : 630, 700, 800 A
Rated frequency : 50 / 60 Hz
Rated conditional short-circuit : 100 kA

current (Iq)

SCPD : Fuse: RS714C, CHINT, 1000 Vac, 800 A, 100 kA

EMC environment : A and B
Control circuits : As below
Rated frequency : 50 / 60 Hz
Rated control circuit voltage (Uc) : 230 / 240 Vac
Rated control supply voltage (Us) : 230 / 240 Vac

Transfer control devices : Controller A and Controller B

Monitored supply deviation : Under-voltage: 160 Vac - 200 Vac (adjustable)

Over-voltage: 240 Vac - 290 Vac (adjustable)

Voltage deviation : ± 10 Vac

Opening time delay : 0 s - 180 s (adjustable)

Closing time delay : 0 s (fixed)Contact transfer time :  $2.7 \text{ x } (1 \pm 10\%) \text{ s}$ 

Off time :  $(2.7 + \text{closing time delay}) \times (1 \pm 10\%) \text{ s}$ 

 $: 4 \times (1 \pm 10\%) s$ 

Total operating time :  $(4 + \text{time delay}) \times (1 \pm 10\%) \text{ s}$ Return transfer time :  $(4,2 + \text{time delay}) \times (1 \pm 10\%) \text{ s}$ 

# **TESTS**

# Test requirements

EN 60947-6-1:2005

EN 60947-6-1:2005/A1:2014

#### Test result

The test results are laid down in DEKRA test file 331203900.



#### Additional information

Nomenclature breakdown:

NXZHM - 800 / 4 B

a b c d

a - code denoting the series name: NXZHM

b - code denoting the rated current of frame: 800 A

c - code denoting the number of pole: 3P, 4P (3P+N)

d - code denoting the controller: controller A, controller B

The referred test report is 3312039.50.

The product also complies with IEC 60947-6-1:2005 and A1:2013.

# Conclusion

The examination proved that all requirements were met.

# **Factory location**

Zhejiang Chint Electrics Co., Ltd. No. 1318, Binhai No. 2 Avenue, Economic and Technical Development Zone, Wenzhou, Zhejiang, China