CERTIFICATE

Issued to:
Applicant:
Zhejiang Chint Electrics Co., Ltd.
No. 1, Chint Road,
Chint Industrial Zone,
North Baixiang, Yueqing,
Zhejiang, China

Licensee: Zhejiang Chint Electrics Co., Ltd.

No. 1, Chint Road, Chint Industrial Zone, North Baixiang, Yueqing, Zhejiang, China

Product : Automatic transfer switching equipment (ATSE)

Trade name(s) : CHINT

Type(s)/model(s) : NXZM-400H, NXZM-400S, NXZM-630H and NXZM-630S

The product and any acceptable variation thereto is specified in the Annex to this certificate and the documents therein referred to.

DEKRA hereby declares that the above-mentioned product has been certified on the basis of:

- a type test according to the standard EN 60947-6-1;2005 and EN 60947-6-1;2005/AN;2014
- an inspection of the production location according to CENELEC Operational Document CIG 021
- a certification agreement with the number 2032236

DEKRA hereby grants the right to use the KEMA-KEUR certification mark

The KEMA-KEUR certification mark may be applied to the product as specified in this certificate for the duration of the KEMA-KEUR certification agreement and under the conditions of the KEMA-KEUR certification agreement.

This certificate is issued on 18 June 2018 and expires upon withdrawal of one of the above mentioned standards.

Certificate number: 33-104264

DEKRA Certification B.V.

drs. G.J. Zoetbrood Managing Director Rosa Zhou Certification Manager

© Integral publication of this certificate is allowed

ACCREDITED BY THE DUTCH ACCREDITATION COUNCIL







SPECIFICATION OF THE CERTIFIED PRODUCT

Product data

Product : Automatic transfer switching equipment (ATSE)

Trade name(s) : CHINT

Type(s)/model(s) : NXZM-400H, NXZM-400S, NXZM-630H and NXZM-630S

Class of equipment : CB
Utilization category : AC-33B
Number of poles : 3P, 3P+N
Rated voltage (Ue) : 400 / 415 Vac
Rated insulation voltage (Ui) : 1000 V
Rated impulse withstand voltage : 12 kV

(Uimp)

Rated frequency : 50 / 60 Hz

Safety distance : Front / Back: 0 mm,

Left / Right: 100 mm, Up / Down: 100 mm

EMC environment : A and B

Control circuits : As below

Rated frequency : 50 / 60 Hz

Rated control circuit voltage (Uc) : 230 / 240 Vac

Rated control supply voltage (Us) : 230 / 240 Vac

Transfer control devices : Controller A and Controller B

Monitored supply deviation : Under-voltage: 160 Vac - 200 Vac (adjustable)

Over-voltage: 240 Vac - 290 Vac (adjustable)

Voltage deviation : ± 10 Vac

Opening time delay : 0 s - 180 s (adjustable)

Closing time delay : 0 s (fixed)Contact transfer time : $2.3 \text{ x } (1 \pm 10\%) \text{ s}$

Off time : $(2,3 + \text{closing time delay}) \times (1 \pm 10\%) \text{ s}$

Operating transfer time : $3.5 \times (1 \pm 10\%) \text{ s}$

Total operating time : $(3,5 + \text{time delay}) \times (1 \pm 10\%) \text{ s}$ Return transfer time : $(3,5 + \text{time delay}) \times (1 \pm 10\%) \text{ s}$

Product data – type NXZM-400H

Rated operational current (le) : 250, 315, 350, 400 A

Rated short-circuit making capacity : 154 kA

(lcm)

Rated short-circuit breaking capacity : 70 kA

(lcn)

Product data – type NXZM-400S

Rated operational current (le) : 250, 315, 350, 400 A

Rated short-circuit making capacity : 105 kA

(Icm)

Rated short-circuit breaking capacity : 50 kA

(lcn)

Product data – type NXZM-630H

Rated operational current (le) : 400, 500, 630 A

Rated short-circuit making capacity : 154 kA

(lcm)

Rated short-circuit breaking capacity : 70 kA

(Icn)



Product data – type NXZM-630S

Rated operational current (le) : 400, 500, 630 A

Rated short-circuit making capacity : 105 kA

(lcm)

Rated short-circuit breaking capacity : 50 kA

(Icn)

TESTS

Test requirements

EN 60947-6-1:2005 EN 60947-6-1:2005/A1:2014

Test result

The test results are laid down in DEKRA test file 331203300.

Additional information

NXZM - 630 S / 4 B

a bcde

- a code denoting the series name: NXZM
- b code denoting the rated current of frame: 400 A, 630 A
- c code denoting the short-circuit breaking capacity: S (50 kA), H (70 kA)
- d code denoting the number of pole: 3P, 4P (3P+N)
- e code denoting the controller: controller A, controller B

The referred test report is 3312033.50.

The product also complies with IEC 60947-6-1:2005 and A1:2013.

Conclusion

The examination proved that all requirements were met.

Factory location

Zhejiang Chint Electrics Co., Ltd. No. 1318, Binhai No. 2 Avenue, Economic and Technical Development Zone, Wenzhou, Zhejiang, China