

Outdoor Combined Transformer



JLSZV77-10 Combined Transformer

Applicable standard: IEC 60044-3 Combined Transformer

1. Operation Conditions

- 1.1 Altitude: no more than 1000m
 - 1.2 Ambient temperature: Max. temperature: +40°C; Min. temperature: -25°C;
Daily average temperature: no more than 30°C
 - 1.3 Air conditions: no heavy pollution in air

2. Technical Parameters

Model/type	Rated primary voltage (kV)	Rated secondary voltage (kV)	Rated frequency (Hz)	Rated output of current transformer (VA)	Rated output of voltage transformer (VA)	Accuracy classes of current transformer	Accuracy classes of voltage transformer	Rated insulation level(kV)
JLSZV77-10	10	0.1	50	10	20	0.2S	0.2	12/42/75

Rated primary current of current transformer (A): 5A, 10A, 15A, 20A, 30A, 40A, 50A, 75A, 100A, 150A, 200A, 300A, 400A, 500A, 600A, 800A, 1000A

Rated secondary current of current transformer: 5A

Rated short-time thermal current of current transformer: 100 I_{th} (1000A=80 I_{th})

Rated dynamic stability current of current transformer: 250 I_{1n} (1000A=200 I_{1n})

Pollution level: Class III

Weight: 108kg

3. Outline and Mounting Dimensions

