


电线电缆类

通用橡套软电缆 Common Insulated Tube Flexible Cable



1 执行标准 Executive Standards

通用橡套软电缆广泛适用于额定电压450/750V及以下家用电器、电动工具和各种移动式电器。本公司生产的通用橡套软电缆完全符合JB8735-1998《额定电压450/750V及以下橡皮绝缘软线和软电缆》和GB5013-1997《额定电压450/750V及以下橡皮绝缘电缆》的规定。

Common rubber tube flexible cable is used extensively in household, electric tool and every mobile apparatus of rated voltage 450/750V and below. The cable made by our company tallies totally with the stipulations of GB 8735-1998 “Rated Voltage 450/750V and below Rubber Insulated Flexible Wire and Cable” and that of GB5013-1997 “Rated Voltage 450/750V and below Rubber Insulated Cable” .

2 技术性能 Technical Performance

2.1 YZ型额定电压为300/500V, YC型为450/750V。YH型额定电压不作规定。

Rated voltage of YZ type is 300/500V, YC type is 450/750V. No stipulation is made for YH type.

2.2 电缆长期工作温度为60°C。Long working temperature of cable is 60°C.

2.3 “W”型派生电缆具有耐气候和一定的耐油性能，适用于户外接触油污场合。

“W” type derived cable is with anti-weather and certain anti-oil performance, which is used in places of outdoor touching oil stain.

3 电缆型号、名称及生产范围

Model, designation and manufacturing scope of cable

型号 Model	额定电压 Rated voltage	名称 Name	芯数 Core No.	截面 Section area	用途 Usage
YQ YQW	300/300V	轻型橡套软电缆 Light rubber tube flexible cable	2-3	0.3-0.5	用于轻型移动电器设备和工具 For light mobile apparatus and tool
YZB、YZWB	300/500V	中型橡套扁形软电缆 Medium rubber tube, flat flexible cable	2-6	0.75-6	
245IEC53(YZ)	300/500V	普通强度橡套软线 Common strength rubber tube flexible wire	2-5	0.75-2.5	用于各种移动电器设备和工具 For light mobile apparatus and tool
245IEC57(YZW)		普通氯丁或其它相当的合成胶弹性体橡套软线 Common neoprene or other compound glue elastic rubber flexible wire			
YZ YZW	450/750V	中型橡套软电缆 Medium rubber flexible cable	2-5	4-6	用于各种移动电器设备，能承受较大的机械外力 For each light mobile apparatus, can withstand larger mechanical force outside.
YC			3+1	1.5-6	
			1	1.5-400	
			2	1.5-95	
	3、4	1.5-150			
245IEC66(YCW) YCW	450/750V	重型橡套软电缆 Heavy rubber flexible cable	5	1.5-25	
			3+1	2.5-150	
			2	35-95	
			3	120-150	
			3+1	2.5-150	

ELECTRIC WIRES & CABLE

型号 Model	额定电压 Rated voltage	名称 Name	芯数 Core No.	截面 Section area	用途 Usage
245IEC81(YH)		天然胶护套电焊机 电缆 Natural ebonite sheathed electric welding machine cable			用于二次侧对地电压交流不超过 200V和脉动直流、峰值400V电 焊机用二次侧接线及连接电焊钳 用铜芯橡胶套软电缆
245IEC82(YHF)		氯丁或其它相当的 合成胶弹性体护套 电焊机电缆 Neoprene or other compound sheathed electric welding machine cable	1	16-95	For secondary to earth voltage not over 200V and secondary wiring and pulse DC, peak 400V electric welding machine Cu rubber cable for secondary wiring and electrode holders